



PIAF 12E

ADVANTAGES :

- 5.10m horizontal outreach
- 30% gradeability
- Zero tailswing
- Rotation 2x176°
- A/C electric drive
- Electric and smooth operating system
- Designed and manufactured for heavy duty use
- Easy maintenance

STANDARD FEATURES :

- Non marking solid tires
- Battery 48V 260Ah
- Centralised battery filling
- On board charger H/F
- Access to platform through a gate
- Tilt indicator with buzzer
- Overload indicator
- Steel frame and fiberglass covers
- Flashing light
- Motion alarm
- Slings and lifting lugs
- On board colour LCD diagnostic console
- Hour meter
- Battery charge indicator

OPTIONS :

- Air line to platform
- 110 or 220V plug in the basket
- ACS (Anti-Crushing System)
- Special customer paint
- Gel battery with charger
- Food compatible oil
- Biodegradable oil

	PIAF 12E
Working height	11.83 m (38 ft. 81 in.)
Platform height	9.83 m (32 ft. 25 in.)
Horizontal reach	5.1 m (16 ft. 73 in.)
Lift capacity (2 persons, wind <28 mph)	200 Kg (441 lbs.)
Turntable rotation	352 °
A Platform width	1.1 m (3 ft. 61 in.)
B Platform length	0.8 m (2 ft. 63 in.)
C Length	3.66 m (12 ft. 01 in.)
D Wheelbase	1.55 m (5 ft. 09 in.)
E Width	1.2 m (3 ft. 94 in.)
F Height - stowed	1.98 m (6 ft. 50 in.)
G Ground clearance	0.1 m (0 ft 33 in.)
Turning radius - inside	0.66 m (2 ft. 17 in.)
Turning radius - outside	2.49 m (8 ft. 17 in.)
Drive speed - stowed	6 Km/h (3.73 Mph)
Drive speed - raised	0.8 Km/h (0.50 Mph)
Maximum tilt value	2 °
Weight	4350 Kg ((9590 lbs.)
Gradeability * - stowed	30 %
Max.ground bearing pressure	1569 kN/m ²

CE This product complies with European regulations in force (EN 280). Due to our constant improvement policy, ATN reserves the right to make any modifications without any prior notice.



www.neonhire.co.uk